



[HOME](#) [ABOUT US](#) [SERVICES](#) [PRODUCTS](#) [CONTACT US](#) [SITE TOOLS](#) [GUESTBOOK](#)

[CPU Coolers](#) > Cofan Part #: KE101-D



Active Cooler For Intel Pentium® III
Socket 370 FCPGA and FCPGA2 (up to 1.4 GHz)

[Features](#) [Thermal Characteristics](#) [Heat Sink](#) [Integrated Fan](#) [PDF Document](#) [Miscellaneous](#)

Features

- Rails on bottom of heat sink prevent movement
- Dual Rocker clip design will withstand all shock and vibration tests.
- Light weight
- Blower can be ducted to increase flow of hot air out of chassis

Thermal Characteristics

Thermal Resistance, Plate to Ambient: 0.75°C/W @ 31.2 Watts, 45°C Ambient

Heat Sink

Alloy	Black Anodized 6063 T5 Aluminum
Pedestal Size (L x W)	1.97" x 1.97" (50.0 mm x 50.0 mm)
Pedestal Flatness	3/1000 per linear inch
Thermal Interface Material	Chomerics T725
Mechanical Mounting	Wire Spring Clip

Integrated Fan

Delta Model:	BFB0512HH
Size (LxWxH):	51.0mm x 51.0mm x 15.0mm
Air Flow:	4.59 CFM at 6500 RPM
Air Pressure:	22 mmH2O
Acoustic Noise	45.0 dB
Input Power:	12 VDC, max. 0.32 A
Connector:	3 pin position, Molex 22-01-3037
Tachometer Sensor Output:	Open Collector, TTL Signal, 2 Pulses per revolution
MTBF:	50,000 hrs. at 40° C

[Terms of Use](#)

[PDF Document](#)

Copyright © 1994-2008 Cofan USA, Inc. All Rights Reserved. 